

Generator Set Data Sheet	Model: C900 D5
	Frequency: 50
	Fuel Type: Diesel

Document Number:	DS33-cpgk-RevA
Spec Sheet:	SS11-CPGK
Noise Data Sheet (Open / Enclosed):	ND50-OSHHP / ND50-CS550
Airflow Data Sheet:	AF50-HHP
Derate Data Sheet (Open / Enclosed):	DD50-OSHHP / DD50-CSHHP
Transient Data Sheet:	TD50-HHP

Fuel Consumption	Standby				Prime			
	kW (kVA)				kW (kVA)			
Ratings	720 (900)				656 (820)			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
US gph	10.9	20.1	29.5	39.1	10.1	18.7	26.6	35.4
L/hr	50	92	134	178	46	85	121	161

Engine	Standby Rating	Prime Rating
Engine Manufacturer	Cummins	
Engine Model	QSK23-G3	
Configuration	Cast Iron, In-line 6 Cylinder	
Aspiration	Turbo Charged and After-Cooled	
Gross Engine Power Output, kW/m	768	701
BMEP at Set Rated Load, kPa	2675	2441
Bore, mm	170	
Stroke, mm	170	
Rated Speed, rpm	1500	
Piston Speed, m/s	8.6	
Compression Ratio	16:1	
Lube Oil Capacity, L	95	
Overspeed Limit, rpm	1800 ±50	
Regenerative Power, kW	72	
Governor Type	Electronic	
Starting Voltage	24 Volts DC	
Fuel Flow		
Maximum Fuel Flow, L/hr	685	
Maximum Fuel Inlet Restriction, mm Hg	203	
Maximum Fuel Inlet Temperature (°C)	70	
Air		
Combustion Air, m³/min	53.3	48.7
Maximum Air Cleaner Restriction, kPa	6.2	
Exhaust		
Exhaust Gas Flow at Set Rated Load, m³/min	147.8	135.6
Exhaust Gas Temperature, °C	543	532
Maximum Exhaust Back Pressure, kPa	10.1	

Standard Set-Mounted Radiator Cooling	Standby Rating	Prime Rating
Ambient Design, °C	50	
Fan Load, KW _m	16	
Coolant Capacity (with Radiator), L	89	
Cooling System Air Flow, m3/min @ 12.7mmH2O	1043	
Total Heat Rejection, BTU/min	20965	19196
Maximum Cooling Air Flow Static Restriction mmH2O	19.1	

Open Set Derating Factors Kw (kVA).					
Note: Standard open genset options running at 400V, 150m above sea level. For enclosed product derates, please refer to datasheet - DD50-CSHHP.					
	27°C	40°C	45°C	50°C	55°C
Standby	720 (900)	720 (900)	713 (891.3)	RTF	RTF
Prime	656 (820)	656 (820)	648 (810)	RTF	RTF


Weights*	Open	Enclosed
Unit Dry Weight kgs	6379	N/A
Unit Wet Weight kgs	6521	N/A

* Weights represent a set with standard features. See outline drawing for weights of other configurations


Dimensions			
	Length	Width	Height
Standard open set dimensions	4266	1879	2052
Enclosed set standard dimensions	N/A	N/A	N/A

Outline

Open Set



Enclosed Set



*Note: Outlines are for illustrative purposes only. Please refer to the genset outline drawing for exact representation of this model.

Alternator Data					
Feature Code	Connection ¹	Temp Rise Degrees C	Duty ²	Alternator	Voltage
B667	Wye, 3 Phase	150/125	S/P	HC6H	380-440V

Notes:

Ratings Definitions		
Standby:	Prime (Unlimited Running Time):	Base Load (Continuous):
Applicable for supplying emergency power for the duration of normal power interruption. No sustained overload capability is available for this rating. This rating is applicable to installations served by a reliable normal utility source. This rating is only applicable to variable loads with an average load factor of 80 percent of the standby rating for a maximum of 200 hours of operation per year and a maximum of 25 hours per year at 100% of its standby rating. The standby rating is only applicable to emergency and standby applications where the generator set serves as the back up to the normal utility source. No sustained utility parallel operation is permitted with this rating. (Equivalent to Fuel Stop Power in accordance with ISO3046, AS2789, DIN6271 and BS5514). Nominally Rated.	Applicable for supplying power in lieu of commercially purchased power. Prime power is the maximum power available at a variable load for an unlimited number of hours. A 10% overload capability is available for limited time. (Equivalent to Prime Power in accordance with ISO8528 and Overload Power in accordance with ISO3046, AS2789, DIN6271, and BS5514). This rating is not applicable to all generator set models.	Applicable for supplying power continuously to a constant load up to the full output rating for unlimited hours. No sustained overload capability is available for this rating. Consult authorized distributor for rating. (Equivalent to Continuous Power in accordance with ISO8528, ISO3046, AS2789, DIN6271, and BS5514). This rating is not applicable to all generator set models.

- Limited single phase capability is available from some three phase rated configurations. To obtain single phase rating, multiply the three phase kW rating by the Single Phase Factor³. All single phase ratings are at unity power factor.
- Standby (S), Prime (P) and (C) Continuous ratings.
- Factor for the *Single Phase Output from Three Phase Alternator* formula listed below
- Maximum rated starting kVA that results in a minimum of 90% of rated sustained voltage during starting.

Formulas for calculating full load currents:

Three Phase Output	Single Phase Output
$\frac{kW \times 1000}{Voltage \times 1.73 \times 0.8}$	$\frac{kW \times SingleP \text{ haseFactor} \times 1000}{Voltage}$

See your distributor for more information.

Cummins Power Generation
 Manston Park, Columbus Avenue
 Manston, Ramsgate
 Kent CT12 5BF, UK
 Telephone: +44 (0) 1843 255000
 Fax: +44 (0) 1843 255902
[E-Mail: cpg.uk@cummins.com](mailto:cpg.uk@cummins.com)
[Web: www.cumminspower.com](http://www.cumminspower.com)

Cummins and PowerCommand are registered trademarks of Cummins Inc. AmpSentry is a trademark of Cummins Inc.

Our energy working for you.™
www.cumminspower.com

© 2004-2006 | Cummins Power Generation | Specifications Subject to Change Without Notice

Cummins and PowerCommand are registered trademarks of Cummins Inc. AmpSentry is a trademark of Cummins Inc.