

Technical data TAD732GE

Standby Power

General

In-line four stroke diesel engine with direct injection. Rotation direction, anti-clockwise viewed towards flywheel. Turbocharged, charge air cooled (CAC)

Number of cylinders			6
Displacement, total		litre	7,15
		in ³	436,3
Firing order			1-5-3-6-2-4
Bore		mm	108
		in	4,25
Stroke		mm	130
		in	5,12
Compression ratio			18:1
Dry weight	Engine only	kg	710
	Engine and cooling package	lb	1565
	Engine only	kg	785
	Engine and cooling package	lb	1731
Wet weight	Engine only	kg	751
	Engine and cooling package	lb	1656
	Engine only	kg	826
	Engine and cooling package	lb	1821

Performance		r/min	1500	1800
Standby Power	without fan	kW	183	204,0
		hp	249	277
	with fan	kW	179	197
		hp	243	268
Prime Power	without fan	kW	165	184
		hp	224	250
	with fan	kW	161	176
		hp	218	240
Continuous Power	without fan	kW	148	165
		hp	202	225
	with fan	kW	144	158
		hp	196	215
Torque at rated speed:	Standby Power	Nm	1165	1082
		lbft	859	798
	Prime Power	Nm	1049	974
		lbft	773	718
	Continuous Power	Nm	944	877
		lbft	696	647
Mean piston speed		m/s	6,5	7,8
		ft/sec	21,4	25,7
Effective mean pressure at:	Standby Power	MPa	2,1	1,9
		psi	299	278
	Prime Power	MPa	1,8	1,7
		psi	264	249
	Continuous Power	MPa	1,7	1,5
		psi	241	223
Max combustion pressure at:	Standby Power	MPa	14,9	19,1
		psi	2161	2770
	Prime Power	MPa	14	15,1
		psi	2031	2190
	Continuous Power	MPa	13,3	14,1
		psi	1929	2045
Total mass moment of inertia, J (mR ²)		kgm ²	3,09	
(with flywheel 2,612 kgm ²)		lbft ²	73,2	
Degree of irregularity at:	Standby Power		1:41	1:52
	Prime Power		1:45	1:57
	Continuous Power		1:49	1:63
Residual speed droop at load increase from 0 to 100%		%	adjustable	
Friction Power		kW	9	12
		hp	11,56	16,728

Technical data TAD732GE

Standby Power

Engine noise emission

Test Standards: ISO 3744-1981 (E)

sound power (without fan, intake and exhaust noise)

Tolerans ± 0.75 dB(A)

		r/min	1500	1800
Measured sound power Lw	No load	dB(A)	103	104
	Standby Power	dB(A)	106	108
	Prime Power	dB(A)	105	108
	Continuous Power	dB(A)	105	108
Calculated sound pressure Lp at 1 m	No load	dB(A)	90	91
	Standby Power	dB(A)	92	95
	Prime Power	dB(A)	92	94
	Continuous Power	dB(A)	92	94

Unsilenced exhaust noise

Data calculated as sound pressure Lp.

Assumed microphone distance 1 m

	r/min	1500	1800
Standby Power	dB(A)	116	117
Prime Power	dB(A)	114	115
Continuous Power	dB(A)	114	115

Load acceptance

Test condition: Warm engine. Load acceptance performance can vary due to actual alternator inertia, voltage regulator, type of load and local ambient conditions.

Single step load performance at 1500 rpm

Load (%)	Speed diff (%)		Recovery time (s)		Remaining load (%)	Speed diff (%)		Recovery time (s)	
	Prime	Standby	Prime	Standby		Prime	Standby	Prime	Standby
0-40	5,4	6,0	1,9	1,9	40-100	11,0		4,8	
0-50	6,7	7,4	2,0	2,1	50-100	8,6		4,1	
0-60	8,5	9,6	3,0	3,3	60-100	6,4		3,6	
0-75	13,0	16,4	4,2	4,4	75-100	3,6		2,3	
0-52	7,0		2,0		0-47		7,0		2,0
0-100									
100-0	9,4	9,4	1,9	1,9					

Single step load performance at 1800 rpm

Load (%)	Speed diff %		Recovery time (s)		Remaining load (%)	Speed diff (%)		Recovery time (s)	
	Prime	Standby	Prime	Standby		Prime	Standby	Prime	Standby
0-40	3,4	3,7	1,6	1,6	40-100	5,3		2,5	
0-50	4,0	4,6	1,6	1,8	50-100	4,4		2,4	
0-60	5,0	5,5	1,6	1,8	60-100	3,2		1,8	
0-75	6,2	7,9	2,0	2,2	75-100	2,0	2,3	1,2	2,6
0-80	7,0		2,0		0-73		7,0		2,0
0-100	12,0		3,6						
100-0	5,3	6,5	2,0	2,2					

Technical data TAD732GE

Standby Power

Cold start performance*

	r/min	1500	1800
Without cold start aid (heater flange)	°C	-15	-15
With cold start aid (heater flange)	°C	-30	-30

Derating

The engine may be operated up to 1000 m altitude and 40°C ambient air temperature without derating.
For applications above 1000 m an ECU with automatic derating must be used.

Altitude derating factor < 3000 m	% / m	4% / 500m
Altitude derating factor > 3000 m		6% / 500m
Ambient temperature derating factor	% / °C	2% / 5°C
Humidity	%	No derating

Lubrication system

		r/min	1500	1800
Lubricating oil consumption	Standby Power	liter/h	0,08	0,09
		US gal/h	0,021	0,024
	Prime Power	liter/h	0,08	0,09
		US gal/h	0,021	0,024
Continuous Power	liter/h	0,08	0,09	
	US gal/h	0,021	0,024	
Oil system capacity including filters		liter	34	
		US gal	8,9	
Oil sump capacity:		max	liter	31
			US gal	8,1
		min	liter	24
			US gal	6,2
Oil change intervals/specifications:				
Closed crankcase ventilation	ACEA: E4. API: CH-4, CI-4* full synthetic	h	500	
Open crankcase ventilation	VDS-2. ACEA: E3, E5. API: CG-4, CH-4*	h	500	
Open crankcase ventilation	VDS. ACEA: E2. API: CF, CF-4*	h	250	
Engine angularity limits:		front up	°	10
		front down	°	10
		side tilt	°	10
Oil pressure at rated speed		kPa	480	520
		psi	70	75
Oil pressure shut down switch setting		kPa	200	
		psi	29	
Lubrication oil temperature:		max	°C	110
			°F	230
Oil filter micron size		mm	0,012	

* See also general section in the sales guide

Fuel system

		r/min	1500	1800	
Standby Power					
Specific fuel consumption at:		25%	g/kWh	234	244
			lb/hph	0,379	0,395
		50%	g/kWh	215	220
			lb/hph	0,348	0,356
Prime Power		75%	g/kWh	212	216
			lb/hph	0,344	0,350
		100%	g/kWh	214	220
			lb/hph	0,347	0,356
Specific fuel consumption at:		25%	g/kWh	270	260
			lb/hph	0,438	0,422
		50%	g/kWh	219	225
			lb/hph	0,354	0,364
Continuous Power		75%	g/kWh	213	217
			lb/hph	0,345	0,352
		100%	g/kWh	213	218
			lb/hph	0,345	0,354
Specific fuel consumption at:		25%	g/kWh	258	275
			lb/hph	0,418	0,445
		50%	g/kWh	222	229
			lb/hph	0,360	0,371
		75%	g/kWh	214	218
			lb/hph	0,346	0,353
		100%	g/kWh	212	217
			lb/hph	0,344	0,351
Recommended fuel to conform to		ASTM-D975-No1 and 2-D JIS KK 2204, EN 590			
Total fuel flow		liter/h	360	450	
		US gal/h	95	119	
Feed pump max suction head		m	1,5		
		foot	4,9		
Feed pump pressure		kPa	500		
		psi	72,5		
Fuel filter micron size		mm	0,005		
Prefilter / Water separator micron size		mm	0,063		
Governor type/make, standard		Heinzmann / EDC 4			
Injection pump type/make		PFW 1 P100 52007 / Bosch			
Injection timing std.		°B.T.D.C	2,5		

Technical data TAD732GE

Standby Power

Intake and exhaust system

		r/min	1500	1800	
Air consumption at:	Standby Power	27°C 81°F	m ³ /min cfm	12,4 438	14,42 509
	Prime Power	27°C 81°F	m ³ /min cfm	11,4 403	14,42 509
	Continuous Power	27°C 81°F	m ³ /min cfm	10,5 371	13,43 474
Air intake restriction, clean filter(s)			kPa in wc	1,5 6,0	1,5 6,0
Max allowable air intake restriction			kPa in wc	3,5 14,1	3,5 14,1
Air filter type			Single stage paper cartridge		
Air filter cleaning efficiency			%		≥ 99,9
Heat rejection to exhaust at:	Standby Power		kW BTU/min	144 8189	167 9497
	Prime Power		kW BTU/min	127 7222	146 8303
	Continuous Power		kW BTU/min	113 6426	127 7222
Exhaust gas temperature after turbine at:	Standby Power		°C °F	542 1008	515 959
	Prime Power		°C °F	529 984	495 923
	Continuous Power		°C °F	517 963	478 892
Max allowable back pressure in exhaust line	Standby Power		kPa In wc	3 12,0	3 12,0
	Prime Power		kPa In wc	5 20,1	7 28,1
	Continuous Power		kPa In wc	5 20,1	7 28,1
Exhaust gas flow at:	Standby Power		m ³ /min cfm	35,1 1240	41,8 1476
	Prime Power		m ³ /min cfm	31,9 1125	38,3 1353
	Continuous Power		m ³ /min cfm	28,9 1021	34,7 1225
Max allowable comb. air temp after CAC			°C °F	50 122	50 122
Max allowable pressure drop over CAC			kPa	15	15
Heat rejection to CAC	Standby Power		kW BTU/min	35,9 2042	46,8 2661
	Prime Power		kW BTU/min	32,3 1837	42,1 2394
	Continuous Power		kW BTU/min	29,1 1655	37,9 2155

Cooling system

		r/min	1500	1800	
Heat rejection radiation from engine at:	Standby Power		kW BTU/min	18 1024	20 1137
	Prime Power		kW BTU/min	17 972	19 1081
	Continuous Power		kW BTU/min	16 927	18 1024
Heat rejection to coolant at:	Standby Power		kW BTU/min	85 4840	96 5454
	Prime Power		kW BTU/min	77 4362	87 4919
	Continuous Power		kW BTU/min	69 3913	78 4413
Recommended coolant	Volvo coolant or Volvo anticorrosion additive together with clean fresh water				
Radiator cooling system type		Closed circuit			
Radiator core area (std. size)		m ² foot ²	0,716 7,71		
Radiator core thickness (std. size)		mm in	55 2,17		

Technical data TAD732GE

Standby Power

Cooling system		r/min	1500	1800
Intercooler core area (std. size)		m ²	0,46	
		foot ²	4,95	
Intercooler core thickness (std. size)		mm	50	
		in	1,97	
Fan diameter		mm	770	
		in	30,31	
Fan power consumption		kW	4,2	7,3
		hp	6	10
Fan drive ratio			1 : 1,0	
Coolant capacity,		engine	liter	9,8
			US gal	2,59
std radiator with hoses			liter	27,3
			US gal	7,21
Coolant pump		drive/ratio	1 : 1,73	
Coolant flow with standard system		l/s	3,0	3,6
		US gal/s	0,79	0,95
Maximum external coolant system restriction, including piping		kPa	25	35
		in wc	100	141
Thermostat,		start to open	°C	87
			°F	189
fully open		°C	102	
		°F	216	
Maximum static pressure head		kPa	100	
		in wc	402	
Pressure cap setting on standard radiator		kPa	90	
		in wc	361	
Maximum top tank temperature		°C	105	
		°F	221	
Max. permissible cooling down of engine coolant by radiator		°C	8	
		°F	46	
Shutdown switch setting		°C	113	
		°F	235	
Recommended draw down capacity			10% of total cooling system capacity	

Cooling performance

Cooling air flow and maximum additional external restriction at different radiator air temperatures based on 105°C TTT and 50% antifreeze (radiator and cooling fan, see optional equipment)

Engine speed rpm	Air on temp °C	STANDBY POWER (LTP)		PRIME POWER (PRP)	
		Air flow kg/s	External restriction Pa	Air flow kg/s	External restriction Pa
1500	60	3,7	0		
	55	3,1	150		
	53	3,0	200		
	47	2,5	300		
	37	2,1	400		
	65			3,7	0
	60			3,1	150
	59			3,0	200
	54			2,5	300
	45			2,1	400
1800	61	4,5	0		
	57	4,0	150		
	56	3,8	200		
	53	3,5	300		
	50	3,2	400		
	65			4,5	0
	61			4,0	150
	60			3,8	200
	57			3,5	300
	54			3,2	400

Technical data TAD732GE

Standby Power

Electrical system

		r/min	1500	1800
Voltage and type		24V / 1 polesystem		
Alternator:	make/output	Amp	Iskra / 55	
	tacho output	Hz/alt. Rev	6	
	drive ratio		1:4,07	
Starter motor	make		Melco	
	type		M008T62471	
	kW		5,0	
Starter motor solenoid,	pull current	Amp	2	
	hold current	Amp	2	
Number of teeth on:	flywheel		129	
	cam gear		96	
	starter motor		10	
Cranking current at +20°C		Amp	400	
Crank engine speed at 20°C		rpm	200	
Starter motor battery capacity:	max	Ah	135	
	min at +5°C	Ah	110	
Inlet manifold heater (at 12 V / 24 V)		kW	2 / 3,6	
Power relay for the manifold heater (at 12 V / 24 V)		Amp	150 / 120	